



Jul 11th, 10:30 AM - 10:50 AM

Modelling of Nitrogen Removal in a Free Water Surface Constructed Wetlands of Tibet, China

Lixiao Zhang

Beijing Normal University, zhanglixiao@bnu.edu.cn

Shoujuan Tang

Beijing Normal University

Alexey Voinov

University of Twente

Follow this and additional works at: <https://scholarsarchive.byu.edu/iemssconference>



Part of the [Civil Engineering Commons](#), [Data Storage Systems Commons](#), [Environmental Engineering Commons](#), [Hydraulic Engineering Commons](#), and the [Other Civil and Environmental Engineering Commons](#)

Zhang, Lixiao; Tang, Shoujuan; and Voinov, Alexey, "Modelling of Nitrogen Removal in a Free Water Surface Constructed Wetlands of Tibet, China" (2016). *International Congress on Environmental Modelling and Software*. 82.

<https://scholarsarchive.byu.edu/iemssconference/2016/Stream-D/82>

This Event is brought to you for free and open access by the Civil and Environmental Engineering at BYU ScholarsArchive. It has been accepted for inclusion in International Congress on Environmental Modelling and Software by an authorized administrator of BYU ScholarsArchive. For more information, please contact scholarsarchive@byu.edu, ellen_amatangelo@byu.edu.

Modelling of Nitrogen Removal in a Free Water Surface Constructed Wetlands of Tibet, China

Lixiao Zhang^a, ShoujuanTang^a, Alexey Voinov^b

^aState Key Joint Laboratory of Environmental Simulation and Pollution Control, School of Environment, Beijing Normal University, Beijing 100875, China.

^aFaculty of Geo-Information Science and Earth Observation (ITC), University of Twente, P.O. Box 6, 7500 AA Enschede, The Netherlands

Presenting author: zhanqlixiao@bnu.edu.cn

Abstract: The construction of free-water surface constructed wetland (FWSCW) for wastewater treatment at high altitude region has being tried in Tibet Autonomous Region, an area with extremely cold weather and low air pressure. The FWSCW was designed to receive nitrogen loading of about 8.00 kg/ha/d and hydraulic loading of 546m³/ha/d. This study aims to develop a model for estimating nitrogen (N) dynamics in this constructed wetland situated in Maizhokunggar county alongside Lhasa river. To ensure stable temperature for healthy biological actions, a passive solar house was built. The major nitrogen transformation processes considered in this study were mineralization, nitrification, denitrification, plant uptake, plant decaying and sedimentation. The modeling results indicated a good fit between the simulated and observed data. The model shows that building of solar house could increase the efficiency of nitrogen removal. With the aid of solar house, the removal rate of total nitrogen increased from 60.26%, 65.69%, 61.75%, 56.18%, to 65.08%, 69.09%, 66.10%, 61.82% during the seasons of spring, summer, autumn and winter, respectively.

Keywords: nitrogen removal; constructed wetland; Stella; solar house; Tibet.